

**PRODUCT IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**CROWN KEROSENE**  
**NEW MSDS DATE:** 09/20/2000

**DATE:** 09/20/00  
PAGE 1 OF 7

### **MATERIAL SAFETY DATA SHEET**

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1.  
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)  
IMPORTANT: Read this MSDS before handling & disposing of this product.  
Pass this information on to employees, customers, & users of this product.

#### **SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY**

**PRODUCT IDENTITY:** **CROWN KEROSENE**  
**COMPANY IDENTITY:** PACKAGING SERVICE CO., INC.  
**COMPANY ADDRESS:** 1904 MYKAWA ROAD / P O Box 875  
**COMPANY CITY:** PEARLAND, TX 77581  
**COMPANY PHONE:** 1-281-485-1458  
**CHEMTREC PHONE:** 1-800-424-9300

#### **SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

**CONTAINS:**

95-100% HEAVY ALIPHATIC SOLVENT NAPHTHA (\*64742-96-7, 8008-20-6)

K1D001

#### **SECTION 3. HAZARDS IDENTIFICATION**

**RISK STATEMENTS:**

Combustible Liquid

R36/37/38 Irritating to eyes, respiratory system and skin.

R20/65 Harmful by inhalation may cause lung damage if swallowed.

**SAFETY STATEMENTS:**

Keep away from ignition sources. Wear proper protective equipment.

**PRODUCT IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**NEW MSDS DATE:** 09/20/2000 **CROWN KEROSENE**

**DATE:** 09/20/00  
**PAGE 2 OF 7**

#### **SECTION 4. FIRST AID MEASURES**

**EYE CONTACT:**

For eyes, flush with plenty of water for 15 minutes & get medical attention.

**SKIN CONTACT:**

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

**INHALATION:**

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.

**SWALLOWING:**

If swallowed, CALL A PHYSICIAN IMMEDIATELY! Do NOT induce vomiting. Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal.

K1D001

#### **SECTION 5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:**

NFPA Class B extinguishers (Carbon Dioxide or foam) for Class IIIA liquid fires.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Water spray may be ineffective on fire but can protect fire fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES:**

**COMBUSTIBLE!**

Keep container tightly closed. Isolate from oxidizers, heat, & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

**CONTAINMENT TECHNIQUES:**

Stop spill at source. Dike area & contain.

**CLEAN-UP PROCEDURES:**

Clean up remainder with absorbent materials. Mop up & dispose of.

**PRODUCT IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**NEW MSDS DATE:** 09/20/2000 **CROWN KEROSENE**

**DATE:** 09/20/00  
**PAGE 3 OF 7**

### **SECTION 7. HANDLING AND STORAGE**

#### **HANDLING:**

Isolate from oxidizers, heat, & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld. Empty container very hazardous! Continue all label precautions!

#### **STORAGE:**

Store large amounts in structures made for OSHA Class IIIA liquids. Keep container tightly closed & upright when not in use to prevent leakage.

K1D001

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION:**

#### **EXPOSURE CONTROLS:**

Use vapor, mist gas mask within use limits, or ventilate to keep vapors of this material below 2mg/cu m. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment.

#### **VENTILATION:**

LOCAL EXHAUST	: Necessary
MECHANICAL (GENERAL)	: Acceptable
SPECIAL	: None
OTHER	: None

#### **PERSONAL PROTECTIONS:**

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

#### **WORK & HYGIENIC PRACTICES:**

Provide readily accessible eye wash stations & safety showers. Wash at end of each workshift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

**PACKAGING SERVICE CO., INC.**  
**PRODUCT IDENTITY: CROWN KEROSENE**  
**NEW MSDS DATE: 09/20/2000**

**DATE: 09/20/00**  
**PAGE 4 OF 7**

### SECTION 9. PHYSICAL DATA

APPEARANCE: Liquid, Water-White  
Various Colors if dyed

ODOR: Mild

BOILING RANGE: 208 222 247 C / 407 432 478 F

AUTO IGNITION TEMPERATURE: 260 C / 500 F (Lowest Component)

LOWER FLAMMABLE LIMIT IN AIR (% by vol): .9

FLASH POINT (TEST METHOD): 79 C / 175 F (PM)

FLAMMABILITY CLASSIFICATION: Class IIIA

GRAVITY @ 60 F:

API: 44.1

SPECIFIC GRAVITY (Water=1): .806

POUNDS/GALLON: 6.714

VOC'S (>0.44 Lbs/Sq In): 0.0 Vol. % / 0.0 g/L / 0.000 Lbs/Gal

TOTAL VOC'S (TVOC): 100.0 Vol. % / 806.0 g/L / 6.713 Lbs/Gal

NONEXEMPT VOC'S (CVOC): 100.0 Vol. % / 806.0 g/L / 6.713 Lbs/Gal

HAZARDOUS AIR POLLUTANTS (HAPS): 0.0 Wt. % / 0.0 g/L / 0.000 Lbs/Gal

VAPOR PRESSURE (mm of Hg)@20 C .2

NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) .2

VAPOR DENSITY (air=1): 6.1

WATER ABSORPTION: Negligible

REFRACTIVE INDEX: 1.448

### SECTION 10. STABILITY & REACTIVITY

#### STABILITY:

Stable

#### CONDITIONS TO AVOID:

Isolate from oxidizers, heat, & open flame.

#### MATERIALS TO AVOID:

Isolate from strong oxidizers such as permanganates, chromates & peroxides.

#### HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Carbon Dioxide from burning.

#### HAZARDOUS POLYMERIZATION:

Will not occur.

K1D001

### SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS #	TWA (OSHA)	TLV (ACGIH)	HAP
----------	-------	------------	-------------	-----

Heavy Aliphatic Solvent Naphtha	*64742-96-7	5 mg/m3	5 mg/m3	No
---------------------------------	-------------	---------	---------	----

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%. Using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Cumene, Polycyclic Aromatics

**PRODUCT IDENTITY:** PACKAGING SERVICE CO., INC.  
**NEW MSDS DATE:** 09/20/2000  
**CROWN KEROSENE**  
**K1D001**

**DATE:** 09/20/00  
**PAGE 5 OF 7**

**SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)**

<b>MATERIAL</b>	<b>CAS #</b>	<b>CEILING</b>	<b>STEL (OSHA/ACGIH)</b>
	None Known		None Known

**ACUTE HAZARDS**

**EYE & SKIN CONTACT:**

Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

**INHALATION:**

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

**SWALLOWING:**

Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

**SUBCHRONIC HAZARDS/CONDITIONS AGGREGATED**

**CONDITIONS AGGREGATED:**

Persons with severe skin, liver or kidney problems should avoid use.

**CHRONIC HAZARDS**

**CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

Leukemia been reported in humans from Benzene. Absorption thru skin may be harmful.

**PRODUCT IDENTITY:** **PACKAGING SERVICE CO., INC.**  
**CROWN KEROSENE**  
**NEW MSDS DATE:** 09/20/2000

**DATE:** 09/20/00  
**PAGE 6 OF 7**

## **SECTION 12. ECOLOGICAL INFORMATION**

### **MAMMALIAN INFORMATION:**

<b>MATERIAL</b>	<b>CAS #</b>	<b>LOWEST KNOWN LETHAL DOSE DATA</b> <b>LOWEST KNOWN LD50 (ORAL)</b>
Heavy Aliphatic Naphtha	*64742-96-7	20000.0 mg/kg (Guinea Pigs)

### **AQUATIC ANIMAL INFORMATION:**

No marine environmental information is available on this product.

### **MOBILITY:**

This material is a mobile liquid.

### **DEGRADABILITY:**

This product is nonbiodegradable.

### **ACCUMULATION:**

This product does not accumulate or bio-magnify in the environment.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If questions exist, contact the appropriate agencies.

## **SECTION 14. TRANSPORT INFORMATION**

DOT SHIPPING NAME: BULK: Petroleum Distillates, n.o.s., Combustible liquid, UN1268, PG-III  
Combustible liquid. Not DOT regulated on trucks in containers of < 119  
gallons.

DRUM LABEL: None (Combustible Liquid)

IATA / ICAO: None

IMO / IMDG: None

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

**PACKAGING SERVICE CO., INC.**  
**PRODUCT IDENTITY: CROWN KEROSENE**  
**NEW MSDS DATE: 09/20/2000**

**DATE: 09/20/00**  
**PAGE 7 OF 7**

K1D001

## SECTION 15. REGULATORY INFORMATION

### EPA REGULATIONS:

**SARA SECTION 311/312 HAZARDS:** Acute, Fire

All components of this product are on the TSCA list.  
This material contains no known products restricted under SARA Title III,  
Section 313 in amounts greater or equal to 1%.

SARA TITLE III INGREDIENTS	CAS#	WT. % (REG. SECTION)	RQ(LBS)
None			

### INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries:  
Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

## SECTION 16. OTHER INFORMATION

### HAZARD RATINGS:

HEALTH (NFPA): 1  
HEALTH (HMIS): 1  
FLAMMABILITY: 2  
REACTIVITY: 0

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

### EMPLOYEE TRAINING:

Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

### NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications.

All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

