DATE PRINTED: 12/01/2004 Zen Seeker PAGE 1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME
W.M. BARR & COMPANY, INC.

ADDRESS 2105 Channel Ave. Memphis, TN 38113

EMERGENCY TELEPHONE #1

EMERGENCY CONTACT W.M. Barr Technical Services

EMERGENCY INFORMATION
"3E" 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.
SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATION

INVENTORY ITEM #
GKKH99991

PRODUCT NAME KS KLEAN HEAT 1 GL

REVISED BY W.M. Barr Technical Services

REVISION DATE 6/11/2003

	•												
SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS													
			CARCII	NOGENIC	TY								
SUBSTANCE DESCRIPTION	PERCENT	CAS#	NTP ACG	IH OSHA	IARC								
Low Odor High Flash Hydrocarbo	100		N N	N	N								
SECTION 3. REGULATORY INFORMATION													
EXPOSURE	E LIMITS/REGULAT	ORY INFORMAT	ION										
SUBSTANCE DESCRIPTION	REG.AGCY U/M	TWA	STEL	CEIL	SKIN	PEL							
Low Odor High Flash Hydrocarbo	ACGIH PPM OSHA PPM	N/E N/E	N/E N/E	N/E N/E	N N	N/E N/E							

ADDITIONAL REGULATORY INFO
The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)
Ingredients in this product are not listed on California's Prop 65
list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

 ${\tt SEC.~313~SUPPLIER~NOTIFICATION}$  The following information must be included in all MSDS that are copied and distributed for this material.

This product contains no chemicals subject to the reporting requirements of SARA III: Section 313.

DATE PRINTED: 12/01/2004 Zen Seeker PAGE

SECTION 3. REGULATORY INFORMATION (CONTINUED)

HAZARD COMMUNIÇATION STANDARD

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 4. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS
May cause dizziness, headache, watering of eyes, eye irritation, weakness, nausea, muscle twitches, and depression of central nervous system. Severe overexposure may cause convulsions, unconsciousness,

SKIN CONTACT ACUTE EXPOSURE EFFECTS None known.

EYE CONTACT ACUTE EXPOSURE EFFECTS May cause irritation.

INGESTION ACUTE EXPOSURE EFFECTS
Harmful or fatal if swallowed. May cause nausea, weakness, muscle twitches, gastrointestinal irritation, diarrhea, unconsciousness, convulsions, and death.

CHRONIC EXPOSURE EFFECTS
Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause skin irritation, anemia, bone marrow damage, liver damage, and iaundice.

PRIMARY ROUTE OF EXPOSURE Inhalation, ingestion, and dermal.

SECTION 5. FIRST AID MEASURES

INHALATION
If user experiences breathing difficulty, move to air free of
vapors. Administer oxygen or artificial respiration until medical
assistance can be rendered.

SKIN CONTACT
Wash with soap and water.

EYE CONTACT Flush with large quantities of water for at least 15 minutes. If irritation from contact persists, get medical attention.

INGESTION
DO NOT induce vomiting. Call your poison control center, hospital
emergency room, or physician immediately.

DATE PRINTED: 12/01/2004 Zen Seeker PAGE 3

SECTION 5 FIRST AID MEASURES (CONTINUED)

NOTE TO PHYSICIAN
This formula is registered with POISINDEX.
Call your local poison control center for further information.

SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE HMIS NFPA 2 HEALTH 1 2 2 FLAMMABILITY 0 0 REACTIVITY OTHER G NA

FLASH METHOD

FLASH POINT 142.00 F

61.11 C

LOWER EXPLOSION LIMIT

GENERAL COMMENTS OSHA FLAMMABILITY: Class II

EXTINGUISHING METHOD
Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES
Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS
CAUTION! COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL
OTHER SOURCES OF IGNITION.

7 ACCIDENTAL RELEASE MEASURES

CLEAN-UP
Keep unnecessary people away; isolate hazard area and deny entry.
Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

 $\ensuremath{\mathsf{WASTE}}$  DISPOSAL Dispose in accordance with applicable local, state and federal regulations.

DATE PRINTED: 12/01/2004 Zen Seeker PAGE

SECTION 8. HANDLING AND STORAGE

**STORAGE**Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING
Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

SECTION 9. TRANSPORT INFORMATION

TRANSPORTATION

Domestic: Petroleum Distillates

IMDG/IMO: Petroleum Distillates, Flash point above 61 degrees C

SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION PROTECTION
Use only with adequate ventilation to prevent build-up of vapors.
Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

RESPIRATORY PROTECTION
For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors vapors.

**SKIN PROTECTION**Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION
Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION Various application methods can dictate use of additional protective various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

VOLATILE % by weight

DATE PRINTED: 12/01/2004 Zen Seeker PAGE

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES (CONTINUED)

BOILING POINT GT 316.00 F

157.77 C BOILING RANGE: 316 F - 360 F

VAPOR DENSITY (Air = 1.0) Heavier than air

EVAPORATION RATE Slower than ether

BULK DENSITY 6.380 lbs/gal at 75 F

pH FACTOR N/E

PHOTOCHEMICALLY REACTIVE

MAX V.O.C. 800 grams per liter (excluding exempt solvents and water)

MAX VAPOR PRESSURE (of the V.O.C.) 2mm Hg at 20 degrees C

SECTION 12. STABILITY AND REACTIVITY

INCOMPATIBILITIES
Incompatible with strong oxidizing agents.

DECOMPOSITION
Decomposition may produce carbon monoxide and carbon dioxide.

POLYMERIZATION Will not occur.

STABILITY Stable.

SECTION 13. ADDITIONAL INFORMATION

IMPORTANT NOTE
The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

LEGEND:

PPM = parts per million

MG/M3 = milligrams per cubic meter

N/E or NE = none established

GT = greater than

N/A or NA = not applicable

TCC = tag closed cup

TOC = tag open cup

PMCC = Pensky-Martens closed cup

IDLH = Immediately Dangerous to Life and Health

DATE P	RINTED:	12/01/2004 Zen Seeker	e =			PAGE	6	
		SECTION	13.	ADDITIONAL	INFORMATION		 	 

\*\*\*END OF MSDS\*\*\*

