UNITED STATES PATENT OFFICE

JOSEPH A. WYLER, OF ALLENTOWN, PENNSYLVANIA, ASSIGNOR TO TROJAN POWDER COMPANY, A CORPORATION OF NEW YORK

ARTIFICIAL FUEL

No Drawing.

Application filed January 9, 1928. Serial No. 245,627.

My invention relates to improvements in ar- which is relatively poor, although by my tificial fuel, and more particularly relates to an improved solid and infusible alcohol fuel. The principal object of my invention is to 5 provide a solid fuel which will not melt during its burning, and which will burn without leaving more than a small amount of residue. One of the objects of my invention is to enable an infusible solid product to be 10 made from an alcohol or a mixture of alcohols that will remain solid during combustion, and that will burn completely without leaving any substantial amount of ash or other residue.

It is well known that solidified products may be made from methyl or from ethyl alcohol, or from mixtures of these two alcohols, by the use of metallic soaps as solidifying agents, and it is also well known that related 20 solidified products may be made from alcohols by the use of nitrocellulose as a solidifying agent. My invention relates to improved products containing neither metallic soaps nor nitrocellulose, and possessing many ad-25 vantages over such solidified products as

have been previously made by the use of known solidifying agents.

I have discovered that when nitrostarch is dissolved in a suitable solvent, such as com-30 mercial 95% methyl alcohol for example, and when such solution is admixed with an alcohol containing a suitable amount of water or other equivalent precipitating agent, solidified products may be obtained possessing 35 greater homogeneity than is possible by the use of nitrocellulose as a colloiding agent, and in addition possessing very desirable properties of firmness of texture and uniformity of burning. One significant ad-40 vantage of my present products, as compared with the nitrocellulose products previously made, is the materially higher content of nitrated product which it is possible to have present in the solidified mixture, without ob-45 taining notable lack of homogeneity or variation in texture. Using nitrocellulose, products containing a high percentage of the nitrated cellulose tend to be very spongy, as compared with products containing a like

present invention I may obtain products containing from 10% to 20% of nitrostarch if desired, without such products being noticeably heterogeneous or "stringy".

As an example of the procedure which I

prefer to follow in the preparation of solidified alcohol products by my present invention, I may dissolve 12 parts by weight of nitrated starch of a nitrogen content of 60 13.50% in 72 parts by weight of commercial 95% methyl alcohol. The nitrostarch will be found to dissolve readily in the methyl alcohol, and will give a slightly opalescent solution. To the above solution represent- 65 ing 84 parts by weight I may add 8 parts by weight of commercial 95% ethyl alcohol, the two liquids being preferably added together rapidly with vigorous stirring. The resulting product is an opalescent liquid, of some- 70 what increased viscosity as compared with the alcohol used in its preparation, and is now ready to be subjected to the final solidifying step. To 92 parts by weight of the above product, I next add 9 parts by weight of 75 water, this water being preferably added in a fine stream, or as a spray of fine droplets, the alcohol mixture being meanwhile gently agitated by shaking, but preferably not being stirred, as stirring or whipping tends to 80 break up the uniform colloidal condition of the resulting "gel".

Upon completion of the addition of water, the product will be found to be a solid product of slightly cellular texture, and of fair 85 firmness or coherence. Upon being ignited the product burns uniformly with hot smokeless flame, without melting, and burns completely without leaving more than a very slight amount of carbonaceous residue, the quantity of such residue being so small as to be wholly unobjectionable. As the 72 parts of commercial 95% methyl alcohol used in the preparation of the above product rep- 95 resents 67 parts by weight of pure methyl alcohol and 5 parts by weight of water, and as the 8 parts of 95% ethyl alcohol represents 7.4 parts by weight of pure ethyl alcohol and amount of nitrostarch and possess a texture .6 parts by weight of water, the actual per- 100

-				
1	centage composition of the above so product is as follows:			m fii
	Methyl alcohol	6	6.3	po N
5	Ethyl alcohol Water Nitrostarch 13.50% N ₂	 1	4.5 11.9	M E
	Nitrostarch 15.50% N ₂		0.00	M
10	The percentage composition of the water mixture is as follows:	alcol	ol-	
		Per	75.3	a
	Methyl alcohol Ethyl alcohol Water	:	16.4	ti
15			00.0	s
	and 13.5 parts of nitrostarch of nitrogen is used to each 100 parts b	13.5 y we	60% ight	s
20	As another example of a produce	mad	e in	i
	accordance with my present invention dissolve 10.5 parts of nitrostarch of 15.6	t 13.	50%	S
25	nitrogen in 54 parts by weight of 95% alcohol, and to this solution I is	\mathbf{nav}	aaa	. (
	12.8 parts by weight of 85% (by ethyl alcohol. The resultant mixtures of the following state of the following stat	ire is	the	. (
	solidified product and has the follow centage composition:	Pe	r cent	(
20	Methyl alcoholEthyl alcohol		64.9	, ,
	Water Nitrostarch		8.3	
38		-	100.0	• '
5	alcohol in place of the 12 parts of n used in the first example above, the of ethyl alcohol and water require	or s s of n % m itros quan ed to ange ch-m ore gular le pr alcoh etain tindiv t the e inj gents ready	olids intro ethy tarch tarch tarch titie pro d bu ethy rigio nts o oduc ol so whic ed re re ridus solu ectio s int y bee	s-lus-tll rryhlnon le
£	may dissolve an amount of nitro	starc	h in	a

nixture of the above solvents so as to have a nal resultant mixture of the following comosition: Vitrostarch containing 12.25% nitrogen 10.6 Methyl alcohol (100% CH_3OH) _____ 41.0 Ethyl alcohol (100% C_2H_5OH) ____ 27.4 75 The above mixture is a thick viscous liquid, which becomes solid upon being exposed to ir to permit the evaporation of a small porion of its contained alcohol. This mixture possesses the desirable characteristic of being sufficiently fluid to permit it to be poured into suitable packing containers and to then solidify to a product of suitable firmness to withstand handling and shipping, by exposng the filled cans, before final closure, to conditions favorable to the evaporation of a small part of the contained alcohol. packaged in two ounce cans, standing in a room at ordinary temperature for a period of from ten minutes to one hour will be sufficient to cause the viscous liquid product to change over to a product of satisfactory firmness. Exposure of the open cans to a stream of warm dry air will also cause the viscous liquid product to "solidify" in from five to 95 fifteen minutes. Although in the above described examples I have referred specifically to the use of nitrostarch of 12.25% and 13.52% N2, I have discovered that by suitable modification of the proportions of the various materials used, I may obtain satisfactory solidified products by the use of nitrostarch having a wide range of nitrogen content. It is to be particularly pointed out that although solidified products 105 have been made from alcohol by the use of nitrocellulose, the nitrogen content of the nitrocellulose is recoginzed to be extremely critical, and a variation of as little as onetenth of one per cent in the nitrogen content 110 of the nitrocellulose is considered to lead to the production of products which are com-mercially unsatisfactory, one of the marked factors of superiority of nitrostarch when used in accordance with the disclosure of my present invention being its adaptability over a wide range of nitrogen content.

By "nitrostarch" as used throughout this specification and the claims, is meant nitrated starch having a nitrogen content within the 120 range of 9.00% N₂ to 14.12% N₂, but nitrostarch having a nitrogen content of from 9.50% N_2 to 13.60% N_2 is preferred. The particular type of starch employed in the preparation of the nitrostarch is not significant and substantially equivalent results are obtained from the use of nitrostarch of the desired nitrogen range prepared from such raw materials as corn starch, cassava starch 130 and potato starch.

125

Although I have referred particularly to to the exact methods or products as herein the use of methyl alcohol and ethyl alcohol, my invention is broadly applicable to the use of other alcohols as well, and I have successfully employed isopropyl alcohol, amyl alcohol and others as equivalents of ethyl alcohol with satisfactory results. I have also discovered that certain agents starch. assist in the formation of a gel, either through 10 forming a firmer gel than would be given by an equivalent mixture without the aid of such assisting agent, or through forming a gel in a mixture that would not gel in the absence of such assisting agent. Among the assisting agents which I have found to give the best results are formaldehyde, furfural, hexamethylenetetramine, urea, oleic acid, or mixtures of any two or more of these agents. As an example of the use of such "assisting 20 agents" in the formation of gels in accordance with my present invention the following composition is illustrative:

 Nitrostarch
 13.6

 Methyl alcohol
 63.9

 Ethyl alcohol
 13.2

 Formaldehyde
 2.0

 Weter
 2.7

 Water_____ 7.3 100.0 My present invention enables me to obtain products either possessing marked homogeneity, by the application of the methods already described herein, or to obtain higher 35 cellular products, where such products may for any reason be of advantage. As an example of the method which I may employ in the preparation of a cellular product of decided firmness of texture and relatively high 40 alcohol content I may spray thin layers of the nitrostarch solution with the jellying agent (diluted ethyl alcohol) and having thus caused the formation of droplets, I then cause a thin layer of the original nitrostarch solu-45 tion to flow over the droplets. In this way I seal and strengthen the layer which now has a honeycomb structure and prepare for the imposition of another such layer above it. These layers are built up upon each other to any desired thickness. Another method by which I may build up a porous structure, is that usually used at present in allied industries, i. e. causing the formation of capillary tubules in which an 55 excess of diluted ethyl alcohol is contained, the walls of the tubules consisting of the gelled nitrostarch. Another method by which I may build up a porous nitrostarch is by spraying the nitrostarch solution into a spray of the jellying solution, allowing the gelled droplets to fall a short distance through an air space. Although I have described certain particu-

lar embodiments of my invention, it is to be c5 understood that I do not wish to be limited

described but desire to cover all such changes and modifications as come within the spirit and scope of the appended claims. I claim: 1. An artificial infusible fuel comprising 70 a solidified mixture of alcohol and nitro-2. An artificial infusible ash-free fuel comprising a solidified mixture of methyl alcohol, ethyl alcohol, water and nitrostarch. 3. An artificial infusible fuel comprising a solidified mixture of methyl alcohol, ethyl alcohol, furfural, water and nitrostarch.
In testimony whereof, I have hereunto subscribed my name this 7th day of January, JOSEPH A. WYLER. 85 90 95 100 105 110 115 120